

Standard 2 Piece Guitar Neck Order Form

Base neck price is \$165, up charges for options are included in the form below.

Heel width is 2.196" (approx 2-3/16"). 22 fret necks have an overhang. This neck fits a standard Fender guitar body with a neck pocket 3" long and 5/8" deep. Nut to heel is 18-7/16". The bridge saddles should be around 7-1/8" from the heel of the neck.

Back wood: Flatsawn maple Mahogany Quartersawn maple (+\$25) Birdseye maple (+\$35)
 Black Limba/Korina (+\$25) White Limba/Korina (+\$25) Customer wood (-\$10)

Fingerboard wood: Flatsawn maple Birdseye maple (+\$15) Indian rosewood Madagascar rosewood (+\$10)
 Black ebony (+\$15) Macassar ebony (+\$5) Pau ferro Customer wood (-\$7)

Nut width: 1.625" 1.650" 1.688" 1.700" 1.750"

1.650" is vintage standard. Floyd R2/L2 nut fits 1.625" or 1.650", R3/L3 nut fits 1.688" or 1.700", R5/L5 nut fits 1.750".

Nut style: Flat bottom Curved bottom Floyd platform (\$+20) LSR (+\$15)

Right/Left hand: Right Left

Heel style: Strat (rounded) - 22 Frets Tele (squared) - 22 fret Strat (rounded) - 21 fret Tele (squared) - 21 fret

Peghead style: Wyr6 Wyr33 6-inline paddle Square paddle Custom - add notes below (+\$60 typical)

Truss rod adjust: Micro Top Slotted heel Spoke heel

Slotted heel is vintage standard, micro top is a small access slot in the head.

NOTE: Spoke heel adjust may require body modification!

Back shape: C D SV Asymm Boatneck Fatback

C shape is standard, D shape has more shoulder, SV has less shoulder.

Asymmetric is a combination of SV and C shapes. Boatneck and Fatback are 1" thickness.

Back thickness: .770" .800" .830" .850" .880" .900"

All thicknesses are measured at 1st fret, back shapes taper approx .090" from 1st fret to 12th fret.

.770" is a Wizard thickness, .800" is comfortably thin, .830" is American Standard.

Looking for a really big neck? Choose Boatneck or Fatback for the back shape option.

Keyhole Size: Vintage (11/32") Modern (25/64") Gotoh/Grover (13/32") None

Stepped vintage style available upon request.

Fretwire: 6230 6130 6105 6125 6150 6100 6105SS 6150SS 6100SS None (-\$20)

Wire dimensions - 6230 (.080"x.043"), 6130 (.106"x.036"), 6105 (.090"x.055"), 6125 (.095"x.047"), 6150 (.104"x.047"), 6100 (.110"x.057") - 6105SS, 6150SS, and 6100SS are stainless steel wire and are +\$30 for installation.

Fingerboard radius: 7-1/4" 9-1/2" 12" 16" 7-1/4" to 9-1/2" 9-1/2" to 12" 10" to 16"

7-1/4" is Fender vintage, 9-1/2" is Fender modern, 12" is Gibson, 16" is fast flat, other compound radii are a mixture of vintage and modern. Compound radii are +\$20.

Dot inlay: Standard White Pearl (+\$10) Paua Abalone (+\$10) Black Pearl (+\$10) None

Standard dots for maple fingerboard necks are black. For dark fingerboards dots are cream face and white side. For no face dot necks, standard color side dots are used.

Carbon fiber reinforced: No Yes (+\$30)

Carbon fiber is recommended on necks thinner than .800" thickness at the 1st fret. Two carbon fiber rods are inserted parallel to the truss rod.

Unsanded necks are -\$35.

Customer information

Name:

Address:

Notes:

Standard Shipping Prices

United States: \$11.25
Outside United States: \$21.25

Best Guitar Parts LLC
10715 "A" Street South - Building 18
Tacoma, WA 98444
Phone: (253) 238-0671
Fax: (253) 572-7650
sales@bestguitarparts.com
<http://www.bestguitarparts.com>