

# Standard 10 Degree Tiltback Guitar Neck Order Form

Base neck price is \$175, up charges for options are included in the form below.

Heel width is 2.196" (approx 2-3/16"). 22 fret necks have an overhang. This neck fits a standard Fender guitar body with a neck pocket 3" long and 5/8" deep. Nut to heel is 18-7/16". The bridge saddles should be around 7-1/8" from the heel of the neck. Neck back wood is from a single piece, no scarf joint.

**Back wood:**  Flatsawn maple  Mahogany  Quartersawn maple (+\$35)  Customer wood (-\$10)  
 Black Limba/Korina (+\$30)  White Limba/Korina (+\$30)

**Fingerboard wood:**  Flatsawn maple  Birdseye maple (+\$15)  Indian rosewood  Madagascar rosewood (+\$10)  
 Black ebony (+\$15)  Macassar ebony (+\$5)  Pau ferro  Customer wood (-\$7)

**Nut width:**  1.625"  1.650"  1.688"  1.700"  1.750"

1.650" is vintage standard. Floyd R2/L2 nut fits 1.625" or 1.650", R3/L3 nut fits 1.688" or 1.700", R5/L5 nut fits 1.750".

**Nut style:**  Standard (3/16" wide)  Floyd platform (\$+20)

**Right/Left hand:**  Right  Left

**Heel/Scale:**  Strat - 24-3/4" Scale  Tele - 24-3/4" Scale  Strat - 25" Scale  Tele - 25" Scale

**Peghead style:**  Wyrd6  Wyrd33  6-inline paddle  Square paddle  Custom - add notes below (+\$60 typical)

**Truss rod adjust:**  Micro Top  Slotted heel  Spoke heel

NOTE: Spoke heel adjust may require body modification!

**Back shape:**  C  D  SV  Asymm  Boatneck  Fatback

C shape is standard, D shape has more shoulder, SV has less shoulder.

Asymmetric is a combination of SV and C shapes.

Boatneck and Fatback are 1" thickness.

**Back thickness:**  .770"  .800"  .830"  .850"  .880"  .900"

All thicknesses are measured at 1<sup>st</sup> fret, back shapes taper approx .090" from 1<sup>st</sup> fret to 12<sup>th</sup> fret.

.770" is a Wizard thickness, .800" is comfortably thin, .830" is American Standard.

Looking for a really big neck? Choose Boatneck or Fatback for the back shape option.

**Keyhole Size:**  Vintage (11/32")  Modern (25/64")  Gotoh/Grover (13/32")  None

Stepped vintage style available upon request.

**Fretwire:**  6230  6130  6105  6125  6150  6100  6105SS  6150SS  6100SS  None (-\$20)

Wire dimensions - 6230 (.080"x.043"), 6130 (.106"x.036"), 6105 (.090"x.055"), 6125 (.095"x.047"), 6150 (.104"x.047"), 6100 (.110"x.057") - 6105SS, 6150SS, and 6100SS are stainless steel wire and are +\$30 for installation.

**Fingerboard radius:**  7-1/4"  9-1/2"  12"  16"  7-1/4" to 9-1/2"  9-1/2" to 12"  10" to 16"

7-1/4" is Fender vintage, 9-1/2" is Fender modern, 12" is Gibson, 15" is modern flat, 16" is fast flat, other compound radii are a mixture of vintage and modern. Compound radii are +\$20.

**Dot inlay:**  Standard  White Pearl (+\$10)  Paua Abalone (+\$10)  Black Pearl (+\$10)  None

Standard dots for maple fingerboard necks are black. For dark fingerboards dots are cream face and white side. For no face dot necks, standard color side dots are used.

**Carbon fiber reinforced:**  No  Yes (+\$30)

Carbon fiber is recommended on necks thinner than .800" thickness at the 1<sup>st</sup> fret. Two carbon fiber rods are inserted parallel to the truss rod.

**Unsanded necks are -\$35.**

## Customer information

Name:

Address:

Notes:

### Standard Shipping Prices

United States: \$11.25  
Outside United States: \$21.25

**Best Guitar Parts LLC**  
10715 "A" Street South - Building 18  
Tacoma, WA 98444  
Phone: (253) 238-0671  
Fax: (253) 572-7650  
[sales@bestguitarparts.com](mailto:sales@bestguitarparts.com)  
<http://www.bestguitarparts.com>